



# S2500 SERIES



Varied Service Characteristics  
Versatile IPv6  
Solution Complete  
Security Mechanism



Carrier-Level High  
Reliability  
Layer-3 Routing  
Functions



Advanced Hardware  
Architecture and  
Industry-leading Port  
Density



Supports Maximum 24  
GE RJ45 Ports and 4  
GE SFP Uplink Ports

## Product Overview

BDCOM S2500 Series is a new-generation intelligent gigabit access switch designed for carrier's IP MAN and enterprise networks. Based on the new-generation high-performance hardware and BDROS platform, it supports functions such as ACL, QinQ and QoS. Its simple management mode and flexible installation can meet the requirement of any complicated scenarios.

BDCOM S2500 Series has 2 models:  
S2500-8T2S, S2500-24T4S.

BDCOM S2500 Series

## Product Characteristics

### Carrier-Level Ethernet Access Switch

S2500 Series supports the carrier-level Ethernet-ring protection protocol with less than 50ms recovery time, STP/RSTP/MSTP, backup uplink ports, and LACP link aggregation to cater to the requirements of high reliability of carriers;

S2500 Series has powerful ACL functions to access and control L2-L7 data based on physical port, providing carriers flexible and various policy control methods;

S2500 Series supports In-Service Software Upgrade (ISSU) to ensure the unremitting data forwarding during system upgrade;

S2500 Series supports various L2 multicast functions such as IGMP-snooping, fast-leave and MVR to fully meet the operation requirements of carrier's IPTV.



# Product Characteristics

---

## Comprehensive IPv6 Solutions

S2500 Series supports the IPv6 protocol suite, IPv6 neighbor discovery, ICMPv6 and Path MTU discovery.

S2500 Series supports Ping, Traceroute, Telnet, SSH and ACL on the basis of IPv6, meeting IPv6 networks' equipment management requirements and service control requirements;

## Enhanced QoS

S2500 Series supports priority retagging and complicated flow classification based on VLAN, MAC, source address, destination address, IP or priority, better streamlining carrier's services.

S2500 Series provides flexible bandwidth control policies, supporting port-/flow-based flow limit, ensuring the line speed forwarding of each port.

S2500 Series supports multiple queue schedule algorithms such as SP, WRR and "SP + WRR".

## Security+

Equipment-level security: The advanced hardware infrastructure design realizes the level-based packet schedule and packet protection, prevents DoS-/TCP- related SYN Flood, UDP Flood, Broadcast Storm or large traffic attacks, and supports level-based command line protection, endowing different levels of users with different management permissions.

Perfect security authentication mechanisms: IEEE 802.1x, Radius and BDTacacs+.

S2500 Series supports storm/multicast/unicast limit, ensuring the normal running of equipment in harsh network conditions.

S2500 Series supports perfect ring detection mechanism, ensuring the long-term stable running of network.

S2500 Series supports port isolation within the same VLAN, DHCP-Snooping, and IP + MAC + Port binding.

## Easy Management and Maintenance

S2500 Series supports many management modes such as the CLI, Telnet, SSH, SSL and SNMP.

S2500 Series supports the WEB management mode, which is easy and efficient for installing and debugging the device.

S2500 Series supports FTP,TFTP and SFTP.

S2500 Series supports ISSU (In-Service Software Upgrade).

S2500 Series supports SNMP and BDCOM NMS smart network management platform. The combination realizes automatic equipment discovery, network topology management, equipment configuration management, performance data statistics and analysis and trouble management.

S2500 Series supports Zero Touch Provisioning(ZTP) function to minimize manual operator intervention and helps reduce customers' initial deployment costs.

# Model lists

## S2500-8T2S




- 8-Port Gigabit RJ45
- 2-Port Gigabit SFP

## S2500-24T4S



- 24-Port Gigabit RJ45
- 4-Port Gigabit SFP

# Application Diagram



# Product Specifications

Item	S2500-8T2S	S2500-24T4S	
Interface	8-Port Gigabit RJ45 2-Port Gigabit SFP	24-Port Gigabit RJ45 4-Port Gigabit SFP	
Console	1 RJ45 port, 1 RST button	1 RJ45 port, 1 RST button	
Backplane	20 Gbps	56 Gbps	
Forwarding rate	15 Mpps	42 Mpps	
Chassis	Dimensions (WxDxH)(mm) Weight(KG)(empty)	280x180x44 1.55	440x210x44 2
Package	Dimensions (WxDxH)(mm) Weight(KG)	346x289x92 2.55	555x295x88 3
Power consumption	no-load full-load	<3W 10W	<7W 20W
Power supply	AC: 100V-240V, 50Hz±10%	15W	25W
Total output BTU (1000BTU/H=293W)	51.19	85.32	
Fan number	no		
Noise@25°C(dBA)	0		
MTBF(H)	>200,000		
Forwarding mode	Store-forward		
Flash (MB)	16		
DRAM (MB)	128		
MAC	8K		
Buffer size(Mb)	4.1		
Jumbo frame	9K		
Total SVI	10		

## Features

### VLAN

- 4K Active VLAN
- QinQ & Selective QinQ
- GVRP, Private VLAN
- Voice VLAN

### Spanning Tree

- 802.1D (STP)
- 802.1W (RSTP) and 802.1S (MSTP)
- BPDU guard, root guard and loopback guard

### Multicast

- IGMP v1/2/3
- IGMP Snooping
- IGMP Fast Leave
- IGMP Filter
- MVR

### IP

- Static route
- RIP, OSPF
- 128 routing table
- IPv4/IPv6 dual stack
- DHCP Server/Client/Relay

### QoS

- CAR, HQoS, MAC/IP/TCP/UDP/VLAN/COS/DSCP/TOS based
- QoS, 802.1P/DSCP priority re-labeling, SP, WRR, and "SP+WRR", Tail-Drop, WRED, flow monitoring and traffic shaping

### Security

- Port isolation, Port security, and "IP+MAC+port" binding, MAC sticky, DHCP Snooping and option 82, DAI & IP source guard, PPoE+,
- IEEE 802.1x, Radius and BDTacacs+
- L2/L3/L4 ACL flow identification and filtration Anti-attack from DDoS, TCP's SYN Flood, UDP Flood, etc.
- Broadcast/multicast/unknown unicast storm-control
- MD5, SHA-256, RSA-1024, AES256, etc.

### Reliability

- Static/LACP link aggregation, Interface backup
- EAPS and ERPS
- ISSU

### Management

- Console, Telnet, SSH v1/2, HTTP, HTTPS, SNMP v1/v2/v3, RMON
- TFTP, FTP, SFTP
- NTP
- ZTP(Zero Touch Provisioning)
- SPAN, RSPAN

### Accessories

- Power cord, rackmount kits, console cable, anti-slipping pad

### Environment

- Operating temperature/humidity: 0°C -50°C, 10%-90% non-condensing
- Storage temperature/humidity: -20°C -70°C, 5%-95% non-condensing

### Certification

- CE, FCC, ROHS

# Ordering Information

Item	Description
<b>S2500 Series switch</b>	
S2500-8T2S	8-Port Gigabit RJ45 + 2-Port Gigabit SFP L3-lite Managed Switch (single AC-220V power supply; fanless, 1U, desktop or rack-mounted installation)
S2500-24T4S	24-Port Gigabit RJ45 + 4-Port Gigabit SFP L3-lite Managed Switch (single AC-220V power supply; fanless, 1U, standard 19-inch rack-mounted installation)
<b>Optical Modules</b>	
<b>100M Optical Modules</b>	
FSFP-SX-1310	100M SFP multi-mode (2Km, 1310nm, LC, DDM)
FSFP-LX-15	100M SFP single-mode (15Km, 1310nm, LC, DDM)
FSFP-LX-40	100M SFP single-mode (40Km, 1310nm, LC, DDM)
FSFP-ZX-80	100M SFP single-mode (80Km, 1550nm, LC, DDM)
FSFP-LX-SM1310-20-BIDI	100M SFP single-mode, single fiber (20Km, TX1310/RX1550, LC, DDM)
FSFP-LX-SM1550-20-BIDI	100M SFP single-mode, single fiber (20Km, TX1550/RX1310, LC, DDM)
FSFP-LX-SM1310-40-BIDI	100M SFP single-mode, single fiber (40Km, TX1310/RX1550, LC, DDM)
FSFP-LX-SM1550-40-BIDI	100M SFP single-mode, single fiber (40Km, TX1550/RX1310, LC, DDM)
FSFP-LX-SM1310-80-BIDI	100M SFP single-mode, single fiber (80Km, TX1310/RX1550, LC, DDM)
FSFP-LX-SM1550-80-BIDI	100M SFP single-mode, single fiber (80Km, TX1550/RX1310, LC, DDM)
<b>GE Optical Modules</b>	
GSFP-TX-B	GE SFP-to-RJ45 module
GSFP-SX-D	GE SFP multi-mode(500m,850nm,LC,DDM)
GSFP-LX-10-D	GE SFP single-mode(10Km,1310nm,LC,DDM)
GSFP-LX-20-D	GE SFP single-mode (20Km, 1310nm, LC, DDM)
GSFP-LX-40-D	GE SFP single-mode (40Km, 1310nm, LC, DDM)
GSFP-ZX-80-D	GE SFP single-mode (80Km, 1550nm, LC, DDM)
GSFP-ZX-120-D	GE SFP single-mode (120Km, 1550nm, LC, DDM)
GSFP-LX-SM1310-10-BIDI	GE SFP single-mode, single fiber (10Km, TX1310/RX1550, LC, DDM)
GSFP-LX-SM1550-10-BIDI	GE SFP single-mode, single fiber (10Km, TX1550/RX1310, LC, DDM)
GSFP-LX-SM1310-20-BIDI	GE SFP single-mode, single fiber (20Km, TX1310/RX1550, LC, DDM)
GSFP-LX-SM1550-20-BIDI	GE SFP single-mode, single fiber (20Km, TX1550/RX1310, LC, DDM)
GSFP-LX-SM1310-40-BIDI	GE SFP single-mode, single fiber (40Km, TX1310/RX1550, LC, DDM)
GSFP-LX-SM1550-40-BIDI	GE SFP single-mode, single fiber (40Km, TX1550/RX1310, LC, DDM)
GSFP-LX-SM1490-80-BIDI	GE SFP single-mode, single fiber (80Km, TX1490/RX1550, LC, DDM)
GSFP-LX-SM1550-80-BIDI	GE SFP single-mode, single fiber (80Km, TX1550/RX1490, LC, DDM)
GSFP-LX-SM1490-120	GE SFP single-mode, single fiber (120Km, TX1490/RX1550, LC, DDM)
GSFP-LX-SM1550-120	GE SFP single-mode, single fiber (120Km, TX1550/RX1490, LC, DDM)

Copyright © Shanghai Baud Data Communication Co., Ltd. 2025. All Rights Reserved.

This document is BDCOM Public Information. BDCOM reserves the right to alter, update and otherwise change the information contained in the document from time to time.  
[www.bdcom.cn](http://www.bdcom.cn)

