

# GP3600 Series

## High-density Pizza-box GPON OLT

### Product Overview


BDCOM GP3600 Series complies with ITU-T G.984/G.988 and meets requirements about GPON OLT in Network Access Technical Requirements. It fully supports CTC2.0, automatic discovery and cooperation with ONUs of different manufacturers.

BDCOM GP3600 Series supports the Asymmetric uplink 1.25Gbps/ downlink 2.5Gbps PON transmission rate, efficient bandwidth usage and Ethernet services, helping carriers to provide reliable services to their users.

Its coupling ratio ups to 1:128, and its support of different hybrid ONU networks minimize the carrier's investment.

BDCOM GP3600 Series supports routing functions such as RIP, OSPF and BGP.

BDCOM GP3600 Series ,based on the edge-cutting technologies, is strong in functions and QoS guarantee, SLA and DBA can be easily listed out.



### Product Characteristics

**GPON:** Abiding by ITU-T G.984/G.988, BDCOM GP3600 Series OLT meets relevant requirements of GPON OLT regulated in Network Access Technical Requirements and China Telecom GPON Technical Requirements CTC2.0;

**System Capacity:** GP3600 Series supports 8/16 GPON ports.

**Uplink Interface:** GP3600 Series is equipped with maximum 4 GE SFP ports, 4 GE combo ports and 4 10GE SFP+ ports.

**Dimensions:** 1U, occupies a small space.

**Environmental Protection:** low power consumption and low operating cost.

**Bus Optical Fiber Protection:** the link can be automatically switched when trouble occurs in the optical fiber;

**Power Characteristics:** supports dual-AC, dual-DC and AC/DC power supply. The power supply supports modularized design, hot-swap and EMC-3 standard. It well adapts to the environment.



Support 1.25Gbps uplink and 2.5Gbps downlink bandwidth



Efficient bandwidth usage and Ethernet services



The Splitting ratio ups to 1:128

## Model Lists

### GP3600-08

High-density Pizza-box GPON OLT



- 1 console port
- 1 out-band 10/100M port
- 8 fixed PON ports
- 4 10GE SFP+ ports
- 4 GE SFP ports
- 4 GE TX/SFP combo ports


### GP3600-16

High-density Pizza-box GPON OLT



- 1 console port
- 1 out-band 10/100M port
- 16 fixed PON ports
- 4 10GE SFP+ ports
- 4 GE SFP ports
- 4 GE TX/SFP combo ports

## Application Diagram



# System Performance

Item	GP3600-08	GP3600-16
<b>Service interface</b>		
PON ports	8	16
GE uplink	4 100/1000M SFP + 4 GE SFP/TX	4 100/1000M SFP + 4 GE SFP/TX
10GE uplink	4 10GE SFP+	4 10GE SFP+
Supported GPON SFP module	Class B+, Class C+, Class C++, Class C+++	
<b>Management interface</b>		
RJ45 console	1	
Mini-USB console	1	
Out-of-Band	1	
<b>System capacity</b>		
DRAM (MB)	1024	
Flash (MB)	32	
Backplane (Gbps)	176	
MAC table	40K	
Buffer size (MB)	3	
Jumbo frame (KB)	9	
IPv4 routing table	32K	
IPv6 routing table	8K	
Active VLAN	4,094	
SVI number	512	
Forwarding mode	Store-and-forward	

# Technical Specifications

## Standards

- ITU-T G.984/G.988
- IEEE 802.11D, Spanning Tree
- IEEE 802.1Q, VLAN
- IEEE 802.1w, RSTP
- IEEE 802.3ad physical link static/dynamic aggregation (LACP), Ethernet - II

## VLAN

- Port/IP/Protocol/MAC-based VLAN
- 4K VLAN
- QinQ and flexible QinQ

## Multicast

- L2 multicast
- IGMP snooping
- MLD snooping
- Fast-leave

## Layer 3 Function

- Static route
- RIPV1/v2
- OSPF
- BGP

## QoS

- Backpressure flow control (half duplex)
- IEEE 802.3x flow control (full duplex)
- IEEE 802.1p, CoS
- WRR, SP and FIFO queue schedule
- Limiting the uplink/downlink rate based on each ONU
- DBA and SLA

## Reliability

- Unidirectional Link Detection (UDLD)
- Hot swap of the GPON optical module
- Optical path protection of GPON (type B/C, hand-in-hand)
- Abnormal luminescence ONU detection such as long luminescence
- IEEE 802.3ad LACP

## DHCP Function

- Server/Relay/Client
- DHCP snooping
- DHCP option 66,67,82
- DAI
- IP source guard

## Network Security

- L2~4 ACL
- Flow-based ACL
- MAC limitation
- MAC sticky
- Port isolation
- Packet storm control
- Transmission data encryption on the PON interface
- Anti attack for DDOS, TCP-SYN-flood, UDP-flood, ARP-flood, etc.

## Management

- Various management modes such as CLI, Telnet, SSH, HTTP, SSL and SNMP
- ISSU
- FTP/TFTP
- SPAN/RSPAN
- NTP

## Network Availability

- STP/RSTP/MSTP
- BPDU guard
- EAPS

## Physical Characteristics

Item	GP3600-08	GP3600-16
<b>Power supply</b>		
AC (V)	90 ~ 264	
DC (V)	36~72	
Power slots	2	
Max. consumption (W)	60	70
Total output BTU (note: 1000 BTU/hr = 293W)	204.8	238.9
<b>Cooling system</b>		
Fan number	3	
Air-flow	Left-right	
Noise@25°C(dBA)	< 45	
<b>Appearance</b>		
Chassis Dimensions(WxDxH mm)	442.5 x 304 x 44	442.5 x 304 x 44
Chassis Weight (Kg)(empty)	5.5	5.6
Package Dimensions(WxDxH mm)	576 x 448 x 94	576 x 448 x 94
Package Weight (Kg)	6.4	6.5
<b>Environmental specifications</b>		
Operating Temperature	0~50°C	
Operating Humidity (non-condensing )	10%~85%	
Storage Temperature	-40°C-80°C	
Storage Humidity (non-condensing )	5%~95%	
<b>Accessories</b>		
Parts	Power cord rackmount kits console cable	
<b>Reliability</b>		
MTBF (Hr)	95,000	
Certification	CE, FCC, ROHS	

## Ordering Information

Model	Description
BDCOM GP3600-08	GPON OLT with 8 PON ports (1 console port, 1 out-band 10/100M port, 8 fixed PON ports (excluding the OLT SFP module), 4 GE SFP ports, 4 GE TX/SFP combo ports, 4 10GE SFP+ ports; 2 power slots with 1 hot-swap AC220V power supply; 19-inch rack-mounted installation)
BDCOM GP3600-08-DC	GPON OLT with 8 PON ports (1 console port, 1 out-band 10/100M port, 8 fixed PON ports (excluding the OLT SFP module), 4 GE SFP ports, 4 GE TX/SFP combo ports, 4 10GE SFP+ ports; 2 power slots with 1 hot-swap DC36~72V power supply; 19-inch rack-mounted installation)
BDCOM GP3600-16	GPON OLT with 16 PON ports (1 console port, 1 out-band 10/100M port, 16 fixed PON ports (excluding the OLT SFP module), 4 GE SFP ports, 4 GE TX/SFP combo ports, 4 10GE SFP+ ports; 2 power slots with 1 hot-swap AC220V power supply; 19-inch rack-mounted installation)
BDCOM GP3600-16-DC	GPON OLT with 16 PON ports (1 console port, 1 out-band 10/100M port, 16 fixed PON ports (excluding the OLT SFP module), 4 GE SFP ports, 4 GE TX/SFP combo ports, 4 10GE SFP+ ports; 2 power slots with 1 hot-swap DC36~72V power supply; 19-inch standard rack-mounted installation)
PWR-75-DC	Hot-swap DC power supply for OLT (Max Power 75W, DC-36 ~ -72V input)
PWR-75-AC	Hot-swap AC power supply for OLT (Max Power 75W, AC100~240V input)
OLT-GSFP-B+	OLT SFP module, Class B+ standard, downlink 2.5G/uplink 1.25G, TX wavelength 1490nm, RX wavelength 1310nm, SC interface
OLT-GSFP-C+	OLT SFP module, Class C+ standard, downlink 2.5G/uplink 1.25G, TX wavelength 1490nm, RX wavelength 1310nm, SC interface
OLT-GSFP-C++	OLT SFP module, Class C++ standard, downlink 2.5G/uplink 1.25G, TX wavelength 1490nm, RX wavelength 1310nm, SC interface

Copyright © Shanghai Baud Data Communication Co., Ltd. 2021. All Rights Reserved.

This document is BDCOM Public Information. BDCOM reserves the right to alter, update and otherwise change the information contained in the document from time to time.  
[www.bdcom.cn](http://www.bdcom.cn)

