

# BDCOM WBR42F-10

## Overview

BDCOM WBR42F-10 is a high-efficient outdoor CPE designed for P2P/P2MP connectivity. It complies with IEEE 802.11 Wi-Fi standards and equipped with a built-in dual-polarized high-gain antenna, it delivers reliable wireless bridging over long distances.

WBR42F-10 features a watchdog mechanism for automatic recovery during network disruptions, along with remote management capabilities. Administrators can monitor real-time status, perform firmware upgrades, and initiate reboots from anywhere.

Ideal for long-range wireless backhaul and point-to-multipoint deployments, WBR42F-10 combines high throughput, carrier-grade reliability with efficient maintenance for harsh outdoor environments.



## Key Features

- Support 2.4GHz band
- Up to 300Mbps speed
- 2 Fast Ethernet ports
- More than 1KM distance

## H/W Specification

Model	BDCOM WBR42F-10	
Chipset	MT7628DAN	
Flash	SPI NOR 8MB	
DDR	DDR2 64MB	
WiFi Frequency	2.412~2.484 GHz	
Max rate	300Mbps	
Antenna	Internal 8dBi directional panel antenna (2.4GHz)	

TX Power	802.11b	11M	19±2dBm	1M	20±2dBm
	802.11g	54M	17±2dBm	6M	19±2dBm
	802.11n HT20	MCS7	16±2dBm	MCS0	18±2dBm
	802.11n HT40	MCS7	16±2dBm	MCS0	18±2dBm
Recv Sensitivity	802.11b	11M	-85dBm	1M	-94dBm
	802.11g	54M	-73dBm	6M	-90dBm
	802.11n HT20	MCS7	-71dBm	MCS0	-89dBm
	802.11n HT40	MCS7	-68dBm	MCS0	-86dBm
EVM	802.11a 54M: ≤-25 dB 802.11n MCS7: ≤-28 dB				
PPM	±20ppm				
WAN	1*10/100M WAN				
LAN	1*10/100M LAN				
Power	PoE 24V or DC 12V Max≤3W				
Reset	Press 1 seconds for Pairing Press 10 seconds for Factory resetting				
button	Set Master / Slave mode				
Indicators	SYS, WAN, LAN, WIFI, Signal*4				
Dimension	168×86×43mm				
Weight	180g				
Temperature	Working: -30~55°C Storage: -40~70°C				
Humidity	5~95% (Non-Condensing)				
Protection	IP65				
ESD	Air: ±8KV Touch: ±6KV				
Electrical Surge	Common Mode: 2KV Differential Mode: 1KV				

## S/W Specification

Operating mode	<ul style="list-style-type: none"> <li>· AP mode</li> <li>· Relay mode</li> </ul>
Wireless	<ul style="list-style-type: none"> <li>· Multi SSID (Max: 4) and Hidden SSID</li> <li>· Transmit Power Setting</li> </ul>

	<ul style="list-style-type: none"> <li>· Scheduled WiFi On/Off</li> </ul>
Wireless Safety	<ul style="list-style-type: none"> <li>· WPA/WPA-PSK</li> <li>· WPA2/WPA2-PSK</li> <li>· MAC ACL with Whitelist</li> <li>· Max client limit (Max: 64)</li> <li>· User isolation</li> </ul>
IP Networks	<ul style="list-style-type: none"> <li>· Static IP, DHCP client</li> <li>· 802.1Q VLAN</li> <li>· IPv4 &amp; IPv6</li> <li>· DHCPd, SNMP, NTP client</li> </ul>
Management	<ul style="list-style-type: none"> <li>· SSH, Telnet</li> <li>· Http/Https</li> <li>· SNMP read</li> <li>· Route tracking</li> <li>· Ping watchdog</li> </ul>

## Antenna Specification

Working Frequency	2412~2484 MHz
Gain	8dBi
Polarization mode	Vertical/Horizontal dual polarization
VSWR	<1.8
Beam angle	Horizon: 60° / Vertical: 60°